

NOYES® HiLite and VFI2 Visual Fault Identifiers



VFI2 Visual Fault Identifier



VFI2 Visual Fault Identifier

The NOYES VFI2 and HiLite visible red laser sources from AFL are designed to troubleshoot faults on fiber optic cables. Light generated by these units will escape from sharp bends and breaks in jacketed or bare fibers, as well as poorly mated connectors. They can quickly identify faults in fiber optic jumper cables, distribution frames, patch panels, and splice trays.

The HiLite and VFI2 are an excellent complement to an OTDR because they can locate faults inside the OTDR's dead-zone. Other applications include end-to-end continuity checks, identifying connectors in patch panels and fibers during splicing operations.

Trace cables in messy or un-documented setups. A VFI unit provides a quick means of finding the "other end" from amongst cluttered cables. Simply connect the VFI to one end and look for the visual red light transmitted out the opposite connector.

- HiLite is a miniature key chain mountable (key chain included) fault locating tool.
- VFI2 is a larger hand-sized package offering longer battery runtime.

Fiber Coupled Lasers for Best Test Results: NOYES VFI2 units deliver 1 mW of output power into 9/125 single-mode fiber to ensure long range and exceptional brightness for locating defects in single-mode and multimode fibers.

The VFI2 and HiLite units use a threaded connector adapter interface to support adapter removal for connector cleaning and field changing of adapter styles.

- 2.5 mm adapter accepts PC and angled connectors FC, SC, ST, etc.
- 1.25 mm adapter accepts LC and MU connectors.

A Visible Fault Indicator (VFI) is an essential tool for fiber technicians.

Features

- Visible red laser source, 650 nm
- High power, 1 mW into 9/125 single-mode fiber
- Compact size
- Universal connector interface for quick connection
- 2.5 mm Universal adapter included
- 1.25 mm Universal adapter available

Applications

- Identify fiber faults inside OTDR deadzone
- Identify sharp bends or breaks in fibers
- Identify poorly mated connectors
- Verify AFL FAST™ Connector Installation

NOYES® HiLite and VFI2 Visual Fault Identifiers

Specifications ^a

OPTICAL	VFI2	HILITE
Emitter Type	Laser, Class II FDA 21 CFR 1040.10 and 1040.11, IEC 60825-1:2007-03	
Wavelength	650 nm ±20 nm	
Output Power	1 mW (into single-mode fiber)	
Modulation	2 Hz or CW selected	2 Hz
GENERAL		
Adapter	2.5 mm Universal	
Power	2 AA alkaline batteries (60 hours typical)	1 AAA alkaline battery (16 hours typical)
Operating Temperature	-10 °C to 50 °C, 85 % humidity non condensing	
Storage Temperature	-30 °C to 60 °C, 95 % humidity non condensing	
Size (H x W x D)	14.0 x 6.2 x 3.2 cm (5.5 x 2.4 x 1.3 in)	7.0 x 3.6 x 1.5 cm (2.8 x 1.4 x 0.6 in)
Weight	<200 g (7.06 oz)	50 g (1.75 oz)

Ordering Information

INCLUDES	AFL NO.
VFI2 unit, instruction card, and carrying case	VFI2
HiLite unit, instruction card, and carrying case	HiLite

Available Adapters

DESCRIPTION	AFL NO.
2.5 mm Universal adapter ^b with captivated sleeve	2900-50-0007MR
1.25 mm Universal adapter ^c with captivated sleeve	2900-50-0010MR

Notes:

- a. All specifications valid at 25 °C unless otherwise specified.
- b. 2.5 mm Universal adapter accepts SC, FC, ST, E2000, etc. ferrules.
- c. 1.25 mm Universal adapter accepts LC, MU, etc. ferrules.





Authorized Channel Partner



United States Customer Service 1.800.321.5298 1.603.528.7780 www.AFLglobal.com	Europe, Middle East, Africa Max Penfold Max.Penfold@AFLglobal.com +44 1799 542 840 +44 7802 839 160	Middle East Ahmed El Sakaty Ahmed.ElSakaty@AFLglobal.com +20 106 451 523	Africa (Sub Sahara) Nicholas Cole Nicholas.Cole@AFLglobal.com +44 7702 005 590	Greater China Dai Liu Dai.Liu@AFLglobal.com +86 133 1101 4533	Asia-Pacific (non-China) Saw Biing Huei Biing.Saw@AFLglobal.com +65 9791 3398
--	---	---	---	--	--